FLIGHT SUMMARY REPORT

Flight Number: 97-110

Calendar/Julian Date: 18 June 1997 • 169

Sensor Package: Wild-Heerbrugg RC-10

Airborne Visible and Infrared Imaging

706

Spectrometer (AVIRIS)

Area(s) Covered: Southern California

Investigator(s): Dozier, UCSB; Gamon, Cal State LA; Aircraft #:

Green, JPL; Whitmeyer, U of Illinois

SENSOR DATA

Accession #: 05191 -----

Sensor ID #: 034 099

Sensor Type: RC-10 AVIRIS

Focal Length: 12" -----

304.66 mm

Film Type: Aerochrome IR -----

SO-134

Filtration: Wratten 12 -----

Spectral Band: 510-900 nm -----

f Stop: 11 -----

Shutter Speed: 1/300 -----

of Frames: 84 -----

% Overlap: 60 -----

Quality: Excellent -----

Remarks:

Airborne Science and Applications Program

The Airborne Science and Applications Program (ASAP) is supported by three ER-2 high altitude Earth Resources Survey aircraft. These aircraft are operated by the High Altitude Missions Branch at NASA-Ames Research Center, Moffett Field, California. The ER-2s are used as readily deployable high altitude sensor platforms to collect remote sensing and in situ data on earth resources, celestial phenomena, atmospheric dynamics, and oceanic processes. Additionally, these aircraft are used for electronic sensor research and development and satellite investigative support.

The ER-2s are flown from various deployment sites in support of scientific research sponsored by NASA and other federal, state, university, and industry investigators. Data are collected from deployment sites in Kansas, Texas, Virginia, Florida, and Alaska. Cooperative international scientific projects have deployed the aircraft to sites in Great Britain, Australia, Chile, and Norway.

Photographic and digital imaging sensors are flown aboard the ER-2s in support of research objectives defined by the sponsoring investigators. High resolution mapping cameras and digital multispectral imaging sensors are utilized in a variety of configurations in the ER-2s' four pressurized experiment compartments. The following provides a description of the digital multispectral sensor(s) and camera(s) used for data collection during this flight.

Airborne Visible and Infrared Imaging Spectrometer

The Airborne Visible and Infrared Imaging Spectrometer (AVIRIS) is the second in the series of imaging spectrometer instruments developed at the Jet Propulsion Laboratory (JPL) for earth remote sensing. This instrument uses scanning optics and four spectrometers to image a 614 pixel swath simultaneously in 224 contiguous spectral bands (0.4-2.4 mm).

AVIRIS parameters are as follows:

IFOV: 1 mrad

Ground Resolution: 66 feet (20 meters) at 65,000 feet

Total Scan Angle: 30°

Swath Width: 5.7 nmi (10.6 km) at 65,000 feet

Spectral Coverage: 0.41-2.45 mm

Pixels/Scan Line: 614
Number of Spectral Bands: 224
Digitization: 10-bits
Data Rate: 17 MBPS

	Wavelength	Number of	Sampling
Spectrometer	Range	Bands	Interval
1	0.41 - 0.70 mm	31	9.4 nm
2	0.68 - 1.27 mm	63	9.4 nm
3	1.25 - 1.86 mm	63	9.7 nm
4	1.84 - 2.45 mm	63	9.7 nm

All AVIRIS data is decommutated and archived at JPL and not currently available for public distribution. For further information contact Rob Green at Jet Propulsion Laboratory, 4800 Oak Grove Drive, Mail Stop 183-501, Pasadena, California 91109-8099.

Camera Systems

Various camera systems and films are used for photographic data collection. Film types include high definition color infrared, natural color, and black and white emulsions. Available photographic systems are as follows:

- Wild-Heerbrugg RC-10 metric mapping camera
 - 9 x 9 inch film format
 - 6 inch focal length lens provides area coverage of 16 x 16 nautical miles from 65,000 feet
 - 12 inch focal length lens provides area coverage of 8 x 8 nautical miles from 65,000 feet
- Hycon HR-732 large scale mapping camera
 - 9 x 18 inch film format
 - 24 inch focal length lens provides area coverage of 4 x 8 nautical miles from 65,000 feet
- IRIS II Panoramic camera
 - 4.5 x 34.7 inch film format
 - 24 inch focal length lens
 - 90 degree field of view provides area coverage of 2 x 21.4 nautical miles from 65,000 feet

The U.S. Geological Survey's EROS Data Center at Sioux Falls, South Dakota serves as the archive and product distribution facility for NASA-Ames aircraft acquired photographic and digital imagery. For information regarding photography and digital data (including areas of coverage, products, and product costs) contact EROS Data Center, Customer Services, Sioux Falls, South Dakota 57198 (Telephone: 605-594-6151).


Additional information regarding ER-2 acquired photographic and digital data is available through the Aircraft Data Facility at Ames Research Center. For specific information regarding flight documentation, sensor parameters, and areas of coverage contact the Aircraft Data Facility, NASA-Ames Research Center, Mail Stop 240-6, Moffett Field, California 94035-1000 (Telephone: 650-604-6252).

CAMERA FLIGHT LINE DATA FLIGHT NO. 97-110

Accession # 05191

Sensor # 034

Check	Frame	Time (GMT-hr, min, sec)		Altitude, MSL	
Points	Numbers	START	END	feet/meters	Cloud Cover/Remarks
A - B C - D E - F	4083-4095 4096-4104 4105-4133	19:35:09 20:12:40 20:32:34	19:40:57 20:16:28 20:45:53	67515/20579 68800/20970 69490/21181	Minor-30% cumulus (frames 4086-4094) Minor cumulus (frames 4097-4098) Minor-10% strato-cumulus (frames 4127-4128); 30-100% strato-cumulus (frames
G - H I - J	4134-4146 4147-4156	20:50:09 21:03:38	20:55:52 21:07:55	69600/21214 69450/21168	4129-4133) Clear Clear
K - L	4157-4166	21:14:09	21:18:24	69550/21199	10% strato-cumulus (frame 4157)



FLIGHT 97-110 18 JUNE 1997

